

**BRIDGEPORT**  
**STANDARD**

**MIRROR**

**FINISH**



SOLE MANUFACTURERS

THE **BRIDGEPORT** CO.

WOOD FINISHING

NEW MILFORD CONN U.S.A

NEW YORK.

CHICAGO.

BOSTON.

# BRIDGEPORT STANDARD MIRROR FINISH



NATURAL



LIGHT OAK



DARK OAK (Golden)



RICH WALNUT



CHERRY



MAHOGANY




ROSEWOOD




FOREST GREEN



WEATHERED OAK



GROUND COLOR



FLAT BLACK

## Directions for Use

First, clean thoroughly the surface to be finished, being sure that it is free from grease and dust, and is thoroughly dry and smooth.

If the surface to be finished is very dirty, wash with water and good soap, wipe up with clean water and allow the work to dry well before applying the finish.

Before using the stain, stir thoroughly, and if any thinning is necessary, use turpentine only.

For woodwork and furniture, one coat is generally sufficient, but for floors we advise the use of two coats; where two coats of stain are desired, allow 48 hours between coats, and lightly sandpaper the surface before applying the second coat.



## For New Work

First, prepare the foundation for the finish by filling all open-grained woods, like oak, ash and chestnut, with WHEELER'S PASTE WOOD FILLER, according to the directions on packages, and then finish with two coats of BRIDGEPORT STANDARD MIRROR FINISH.

On close-grained woods, excepting floors, use WHEELER'S SILEX LIQUID WOOD FILLER for preparing the foundation.





## For Floors

Whether open or close-grained wood, fill with WHEELER'S PASTE WOOD FILLER; never use liquid filler on a floor.

For re-finishing old floors which have been varnished or stained, clean the surface thoroughly as stated before; then lightly sandpaper.

If polish or wax has been used on the floor, it should be removed by washing thoroughly with turpentine.

Touch up all bare spots with BRIDGEPORT STANDARD MIRROR FINISH.

Fill all cracks with WHEELER'S CRACK AND CREVICE FILLER.

Lightly sandpaper the whole surface and apply two coats of BRIDGEPORT STANDARD MIRROR FINISH of the desired shade.

If the floor is badly spotted or worn, all the finish should be removed with BRIDGEPORT STANDARD PAINT AND VARNISH REMOVER; then the floor re-finished as directed for new floors.

If, however, the floor is badly spotted and it is not desired to remove the old finish, first clean the floor and apply one coat of ground color, after which apply BRIDGEPORT STANDARD MIRROR FINISH.

## For ReFinishing Painted Floors

First, fill all cracks with WHEELER'S CRACK AND CREVICE FILLER, then apply one coat of ground color and finish with two coats of BRIDGEPORT STANDARD MIRROR FINISH of the shade wanted.

## Bridgeport Standard Mirror Finish

A high grade varnish stain, which produces, in a variety of beautiful colors, a transparent, mirror-like finish.

It is particularly applicable for refinishing woodwork, furniture or floors, the finish on which has become worn or scratched.

Remember that to properly dry the stain, light and air are required.

---

BRIDGEPORT STANDARD MIRROR FINISH is put up in gallon, half-gallon, quart pint and half-pint cans.

It will cover about 300 square feet to the gallon, two coats, or about 500 square feet, one coat.

---

FOR SALE BY

AVERY LIBRARY  
COLUMBIA UNIVERSITY

